



## SW-5101 AQUATICS/TRACK SCOREBOARD SPECIFICATIONS

This one-line LED (light emitting diode) aquatics scoreboard operates seamlessly with Daktronics OmniSport® series controllers or multiple competitors' controllers. The scoreboard displays LANE, PLACE, and TIME information and is available in indoor 120 V AC (-13), indoor 230 V AC (-14), outdoor 120 V AC (-11) and outdoor 230 V AC (-12) models.

### PRODUCT SPECIFICATIONS

**PRODUCT SAFETY APPROVAL:**

ETL listed and tested to CSA standards  
CE label pending

**DIMENSIONS:**

Height 1'-9", Width 9'-0", Depth 6" (533 mm, 2743 mm, 152 mm)

**WEIGHT:**

45 lb (20 kg)

**POWER:**

100 W maximum, 120 V AC (0.8 A) or 230 V AC (0.4 A) configurations available

**CONSTRUCTION:**

Durable, lightweight aluminum for excellent corrosion resistance  
Shipped in one section

**DIGITS:**

All digits are 10" (254 mm) high with seven bar segments per digit. Indoor digits and outdoor digits are red, amber, or alternating rows of red and amber. All digits consist of PanaView® LEDs.

**CAPTIONS:**

All captions are 5" (127 mm) high. All captions and colons are white vinyl. LANE and PLACE captions are applied directly to changeable panels. The TIME caption is applied directly to the display face.

**CABINET COLOR:**

Finish is acrylic black

## SW-5101 PRODUCT SPECIFICATIONS (CONTINUED)

- OPERATING TEMPERATURES:** Display: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius) Controller: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)
- COMPATIBILITY:** The SW-5000 series scoreboards can be controlled by Daktronics OmniSport® 1000, 2000, or 6000 controllers, Colorado Time Systems® (CTS) controllers, Omega® Ares 21 or OSM6 controllers (swim mode only), Omega Scan'O'Vision™ and Finish Lynx® photo finish systems. Please specify when ordering.
- WARRANTY/SERVICE PLAN:** Exclusive Daktronics Gold® plan in the U.S. and Canada (see SP10093 for more information).
- CONTROL CABLE:** A two conductor shielded communication control cable of 22 AWG minimum is required.
- JUNCTION BOX:** A cover plate with mounted 1/4" stereo phono connector and standard 2"x2"x4" outlet box is provided. The connector mates with the connector from the scoreboard controller.
- GENERAL INFORMATION:** Each scoreboard module comes completely assembled. 100% solid state electronics housed in an aluminum cabinet.
- OPTIONS:**
1. Logo/sponsor panel (Standard Sizes: Height 1'-2" by Width 9'-0"; Height 1'-9" by Width 9'-0"; and Height 2'-4" by Width 9'-0")
  2. Electronic message center
  3. Alternate caption colors available (see SL06409)

*Gold® and OmniSport® are registered trademarks of Daktronics, Inc. Colorado Time Systems®, Omega®, Scan'O'Vision™ and FinishLynx are registered trademarks of the owners.*

