

LANE	PLACE	TIME	LANE	PLACE	TIME
1	4	14:54.63	4	2	14:48.17
2	6	15:01.39	5	1	14:47.80
3	5	14:56.24	6	3	14:50.76

## SW-5216 AQUATICS MULTISPORT SCOREBOARD SPECIFICATIONS

This six-line LED (light emitting diode) aquatics scoreboard displays LANE, PLACE and TIME information. The scoreboard is shown in swimming mode. Captions for diving and water polo are also included (see illustrations on the last page). The scoreboard is available in indoor 120 V AC (-13), indoor 230 V AC (-14), outdoor 120 V AC (-11) and outdoor 230 V AC (-12) models.

### PRODUCT SPECIFICATIONS

#### PRODUCT SAFETY

**APPROVAL:** ETL listed and tested to CSA standards  
CE label pending

**DIMENSIONS:** Height 4'-8", Width 18'-0", Depth 6" (1422 mm, 5486 mm, 152 mm)

**WEIGHT:** 330 lb (150 kg)

**POWER:** 800 W maximum, 120 V AC (2.5 A) or 230 V AC (1.3 A) configurations are available

**CONSTRUCTION:** Durable, lightweight aluminum for excellent corrosion resistance  
Shipped in eight sections

**DIGITS:** All digits are 10" (254 mm) high, with seven bar segments per digit. Indoor and outdoor digits are red, amber or alternating rows of amber and red digits. All digits consist of PanaView® LEDs.

**CAPTIONS:** All captions and colons are 5" (127 mm) and composed of white vinyl. LANE and PLACE captions are applied directly to changeable panels. TIME caption is applied directly to the display face.

**CABINET COLOR:** Finish is acrylic black

## SW-5216 PRODUCT SPECIFICATIONS (CONTINUED)

**OPERATING TEMPERATURES:** Display: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius) Controller: 32 to 122 degrees Fahrenheit (0 to 50 degrees Celsius)

**COMPATIBILITY:** The SW-5000 series scoreboards can be controlled by Daktronics OmniSport® 1000, 2000 or 6000 controllers.

**WARRANTY/SERVICE PLAN:** Exclusive Daktronics Gold® plan in the U.S. and Canada (see SP10093 for more information).

**CONTROL CABLE:** A two conductor shielded communication control cable of 22 AWG minimum is required.

**JUNCTION BOX:** A cover plate with mounted 1/4" stereo phono connector and standard 2"x2"x4" (51 mm, 51 mm, 102 mm) outlet box is provided. The connector mates with the connector from the scoreboard control console or external scoreboard interface.

**GENERAL INFORMATION:** Each scoreboard section comes completely assembled. 100% solid state electronics housed in an all aluminum cabinet.

**OPTIONS:**

1. Auxiliary modules to display team scores, event, and heat
2. Logo/sponsor panel (Standard Sizes: Height 1'-2" by Width 9'-0"; Height 1'-9" by Width 9'-0"; and Height 2'-4" by Width 9'-0")
3. Alternate caption colors available (see SL06409)

## SW-5216 PRODUCT SPECIFICATIONS (CONTINUED)

JUDGE SCORE			JUDGE SCORE		
8	1	00:00.81	88	:	00.17
8	8	95:00.89	88	:	47.80
8	8	74:00.00	3.3		4:50.76
			D of D		TOTAL SCORE

**SW-5216 Diving mode**

		TIME HOME	PERIOD	SHOT	TIME GUEST
8	8	08:52.00	2	00	00:40.00
8	8	15:00.19		24	00:00.12
8	8	24:00.00		14	00:00.00
		PENALTY SCORE			PENALTY SCORE

**SW-5216 Water polo mode**

Gold® and OmniSport® are registered trademarks of Daktronics, Inc. Colorado Time Systems®, Omega®, Scan'O'Vision™ and Finishlynx® are registered trademarks of the owners.

